

## DTEC 334 Solvent PP film 170μ

05/2016

### Description

DTEC 334 Solvent PP film is a tear-resistant polypropylenfilm with a special coating for solvent and eco-solvent inks. The coating allows brilliant photo quality printing, short drying time and high saturation. DTEC 334 presentation film is fully waterproof and most scratch resistant. The coating makes it able to achieve high-end presentation quality with bright colours and very good contrast. To avoid fingerprints we advise to wear cotton gloves.

### Application:

RollUp displays, signs for in- and outdoor, POS advertisement, photoreproduction, displays

### Properties

Material:	Polypropylen
Finish:	semi-glossy
Colour:	white
Weight (ISO 536):	130 g/m <sup>2</sup>
Thickness (ISO 534):	170μ
Initial Tensile Strength:	200N / 50mm
Max. Tensil Strength:	155% (at break)
Initial Tear Strength:	1100N / 50mm
Tear Strength:	< 10N / 50mm
Storage Temperature:	10°C - 30°C
Air Humidity:	35% - 65%
Lamination:	cold
Width of roll:	914 / 1371 mm
Length of roll:	30,0m
Flame retardant:	no
Ink type:	Eco Solvent, UV, Latex

### Printing guidelines

Allow material to adapt to room conditions for 24 hours before printing.

Print conditions: best results are obtained between 15-25°C and 35-60% RH. Ink restrictions and heater setting have to be set for specific printer ink combinations to obtain the best results. To achieve the best possible print quality, please make sure that the correct ICC profiles or printer settings are used.

### Disclaimer

All technical data and advice is based on our experience and measured testing that we believe to be reliable. It remains the customer's responsibility to test our products suitability for the purpose intended. The quality of our products is regularly examined, upgraded and developed. We reserve the right, without prior notice, to adjust, upgrade and improve the chemical structures or physical characteristics of their products in accordance with their latest knowledge.