



DTEC 142RAF GreenPrint Film White Matt Rem Airfree

06/2020

Product Description

White matt , pvc-free, polypropylene print film. The film has a transparent removable adhesive and includes air channels for easy application. Particularly used for environmental friendly applications e.g. floor graphics, exhibition stands, POS and signs.

Specifications	
Face film	100µm, white matt, PP - film
Adhesive	Removable, transparent acrylic adhesive, micro air channels
Liner	Double-sided PE-liner, 140g /m ²
Printing	Eco-solvent, UV , Latex inks
Application temp.	Min 10°C
Shelf Life	2 years when stored at 15 to 25°C and ± 50 % relative humidity (in original packaging)
Durability	2 years indoor

Physical Properties

Properties	Average values	Test method
Adhesion power after 24h	8 N / 25mm	Finat 1
Adhesion power direct	3.7 N / 25mm	Finat 9
Fire behavior	Not tested	-
Temperature ranges		
Minimum application temperature:	+ 10°C	
Service temperature range:	15°C to + 40°C	

Printing guidelines

Allow material to adapt to room conditions for 24 hours before printing.

Print conditions: best results are obtained between 15-25°C and 35-60% RH. Ink restrictions and heater setting have to be set for specific printer ink combinations to obtain the best results. To achieve the best possible print quality, please make sure that the correct ICC profiles or printer settings are used.

Disclaimer

All technical data and advice is based on our experience and measured testing that we believe to be reliable. It remains the customer's responsibility to test our products suitability for the purpose intended. The quality of our products is regularly examined, upgraded and developed. We reserve the right, without prior notice, to adjust, upgrade and improve the chemical structures or physical characteristics of their products in accordance with their latest knowledge.