



DTEC 241 GreenLine Laminate Gloss

06/2020

Product Description

DTEC 241 GreenLine Laminate is a transparent glossy Polypropylene, pvc-free, overlamine designed to protect full colour graphics for short term internal applications. Particularly used for environmental friendly applications in combination with DTEC 140 GreenPrint Film. The pressure sensitive adhesive allows a fast and effective processing when laminating from roll.

| Specifications | |
|-------------------|--|
| Face film | 50µm, polypropylene, transparent, glossy |
| Adhesive | Permanent, transparent , acrylic adhesive |
| Liner | One-side siliconised kraft paper, 120g /m ² |
| Application temp. | Min 15°C |
| Shelf Life | 2 years when stored at 15 to 25°C and ± 50 % relative humidity (in original packaging) |
| Durability | 2 year indoor, short term outdoor |

Physical Properties

| Properties | Average values | Test method |
|----------------------------------|------------------|-------------|
| Adhesion after 24h | 19,8 N / 25mm | FINAT 1 |
| Fire behaviour | Not tested | - |
| Temperature ranges | | |
| Minimum application temperature: | + 15°C | |
| Service temperature range: | - 20°C to + 40°C | |

Disclaimer

All technical data and advice is based on our experience and measured testing that we believe to be reliable. It remains the customer's responsibility to test our products suitability for the purpose intended. The quality of our products is regularly examined, upgraded and developed. We reserve the right, without prior notice, to adjust, upgrade and improve the chemical structures or physical characteristics of their products in accordance with their latest knowledge.