

Interlam™

EcoTex™

Interlam™ EcoTex™ is a 4.7 mil (120µ) PP laminating film with a pebble textured finish, coated on one side with a pressure sensitive, aqueous acrylic adhesive that is protected by a bleached Kraft release paper coated on one side with siliconised PE. Interlam™ EcoTex™ is phthalate-free and provides excellent image enhancement for indoor graphics. It has been tested in accordance with DIN 51130 standards and has been awarded an R10 rating.

- THE SCUFF-RESISTANT, PEBBLE TEXTURED FINISH MAKES THIS LAMINATING FILM SUITABLE FOR GRAPHICS WHERE EXTENSIVE HANDLING MAY BE INVOLVED
- IDEAL FOR LAMINATING AND ENCAPSULATING TRADESHOW AND BANNER STAND GRAPHICS, SIGNAGE IN HIGH TRAFFIC AREAS, COUNTER MATS, PLACEMATS, AND OTHER GRAPHICS WHERE A SCUFF-RESISTANT FINISH IS REQUIRED AND COST IS A KEY FACTOR
- IDEAL FOR SINGLE-SIDED LAMINATION DUE TO ITS DIMENSIONAL STABILITY
- OFFERS EXCELLENT UV PROTECTION FOR HIGH QUALITY IMAGES, PHOTOGRAPHIC PRINTS, WALLCOVERINGS, AND SELF-ADHESIVE VINYL

For more information, performance and warranty guide lines please contact your local Drytac office.

© 2019 Drytac Corporation. E&OE.
All other trademarks are the property of their respective owners.

TECHNICAL SPECIFICATION

PRODUCT STRUCTURE

Film	Pebble Textured PP
Adhesive	Aqueous Acrylic (Pressure Sensitive)
Release Liner	Siliconised 1 Side PE Coated Kraft

PRODUCT CHARACTERISTICS

Film Thickness	4.7 mil (120µ) 5.7 mil (145µ)
Adhesive Layer	1 mil (25µ)
UV Protection Factor	Adhesive contains UV stabilisers, which prevent film degradation and provide UV protection to the underlying image
Outdoor Durability	Not Applicable
Service Temperature Range	-4°F to 248°F (-20°C to 120°C)
Peel Strength (20 min, FTM1)	11 N/25mm
Shelf Life	1 year
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

PROCESS SETTINGS

Equipment Type & Temperature	Speed
Roller Laminator Room temperature to 104°F (40°C)	1 ft to 8 ft (0.3m to 2.5m) per minute
Press	Not recommended

DRYTAC®
ADHESIVE SCIENCE

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

30 Driver Road,
Brampton,
Ontario, L6T 5V2,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5601 Eastport Boulevard,
Richmond,
Virginia, 23231,
USA
customerservice@drytac.com
Tel: +1 800.280.6013

www.drytac.com